



Art.-No.: 6.1126.1850  
 6.1126.2450  
 6.1126.3050  
 6.1126.3650  
 6.1126.4850

**1126**

## Masking Tape 80°

### Characteristics

Masking Tape for automotive repair workshops. Suitable for wall-painting on building and construction sites, industrial and car repair applications.

- Good adhesion even on irregular surfaces
- Heat resistant up to 80°C (30 minutes)
- Easy removal without adhesive residue as soon as paint is dry
- Well conformable to most shaped surfaces
- Compatible with most common paints and lacquers
- Removable without breaking
- Hand tearable

### Tech Tip

Recommended to remove within 48 hours.

### Technical Data

Backing	58 g/m <sup>2</sup> natural white saturated crepe paper
Adhesive	Dry natural rubber and resins solvent based
Total thickness	0.125 mm
Adhesion to steel	4.3 N/25mm
Tensile strength MD	85 N/25mm
Elongation at break	7.5 %
Temp. Resistance	80°C (30 min)

### Storage and Transportation

Product shelf life: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use.

