



Art.-No.: 6.1136.1850
 6.1136.2450
 6.1136.3050
 6.1136.3650
 6.1136.4850

1136

Masking Tape 100° WP IR

Characteristics

Waterproofed and infrared resistant high quality masking tape for automotive repair workshops.

Tech Tip

- Very good adhesion
- Resistant to thinners
- Heat resistant up to 120°C (30 minutes), suitable for oven drying (100°C) cycles
- Easy removal without adhesive residue as soon as paint is dry
- Well conformable to most shaped surfaces
- Excellent performances with traditional solvent based and water based paints
- Removable without breaking
- Infrared resistant
- Highly resistant to moisture and water

Technical Data

Backing	75 g/m ² brown saturated crepe paper
Adhesive	Dry natural rubber based and resins solvent based
Total thickness	0.14 mm
Adhesion to steel	5 N/25mm
Tensile strength MD	100 N/25mm
Elongation at break	8 %
Temp. Resistance	120°C (30 min)

Storage and Transportation

Product shelf life: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use.

